



型 式		1RF-LT	2RF-LT	2.8RF-LT	3RF-LT	5RF-LT	7.5RF-LT	10RF-LT	
額定荷重 (Ton)		1	2	2.8	3	5	7.5	10	
標準揚程 (M)		6、8							
捲上速度 (M/min)	50HZ	7	6.3	5.3	5.3	6	4.2	4.3	
	60HZ	8.4	7.5	6.3	6.3	7.2	5	5.2	
捲上馬達 (Kw)		1.5	3.7	3.7	3.7	7.5	7.5	11	
橫行速度 (M/min)	50HZ	17				14			
	60HZ	20				17			
橫行馬達 (Kw)		0.37	0.37	0.37	0.37	0.75	1.1	1.5	
鋼索直徑 (mm)		Φ6	Φ8	Φ10	Φ10	Φ12	Φ14	Φ16	
鋼索掛數		4/2							
概 略 尺 寸 (mm)	E	6M	595	655	780	780	870	920	995
		8M	635	700	830	830	920	970	1045
	F	6M	345	400	530	530	560	610	725
		8M	385	445	580	580	610	660	775
	C	300	360	360	360	420	420	420	
	Φd	37	40	60	60	75	85	100	
	A	370	420	530	530	620	635	770	
	B	200	250	340	340	340	380	425	
H	455	500	550	550	790	850	850		
適用型鋼寬度 (mm)		125~150				150~190	150~190		
淨重 (Kg)	6M	130	210	275	275	490	540	820	
	8M	145	230	300	300	540	590	930	